



UNCOMPRIMISING IN EVERY SENSE™



## iC7si

### 7" STEREO INPUT CEILING-MOUNT LOUDSPEAKER

High performance stereo input loudspeaker that reproduces stereo sound from a single loudspeaker; optimal for spaces where multiple speakers are not practical.

#### KEY FEATURES

- **Integrated Woofer/Baffle Design** Delivers improved low frequency response by employing a larger woofer cone than competitive models of the same diameter.
- **Dual Tweeter Array and Dual Voice Coil Woofer** Provide "Stereo Imaging" from a single speaker
- **Proprietary Bridge-Mounted Tweeter Adjustment Mechanism** Directs the high frequency sounds to the listening area in any direction up to 20° without diffraction.
- **Weather-Resistant Construction** Enables installation in moist environments such as bathrooms, kitchens, saunas, and outdoor areas under eaves
- **Install With Confidence** The best-built loudspeakers deserve the best protection—a Lifetime Limited Warranty.

# iC7si

## 7" STEREO INPUT CEILING-MOUNT LOUDSPEAKER



### iC7si

7" STEREO INPUT LOUDSPEAKER

FG01638

Packaged Individually with round MicroPerf™ Grille

#### RELATED PRODUCTS

CM700 BKT New  
Construction Bracket  
FG01308



CM700 Hole Cover  
FG01309



CE6 Metal Loudspeaker  
Enclosure  
FG00944



### FEATURES

- Integrated baffle/frame assembly increases the cone area for deeper bass than competitive speakers of the same diameter
- 7" injection-molded TCC™ (Talc, Carbon, and Ceramic-filled) woofer cone with butyl rubber surround for deep, low distortion bass response
- Dual pivoting 1" fluid-cooled Teteron® dome tweeters provide ultra-wide dispersion and smooth response
- Bridge-mounted stereo imaging (SI) tweeter array directs the left and right channels at opposing angles to preserve stereo separation
- Paintable, flush-mount MicroPerf™ aluminum grille
- Weather-resistant construction enables installation in wet environments and outdoors under eaves

### SPECIFICATIONS

- Recommended amplifier power: 10 - 125 watts
- Impedance: 8 ohm nominal; 6 ohm minimum
- Frequency response: 55 Hz to 21 kHz +/- 3 dB

### DIMENSIONS

- Frame dimensions (with grille): 9-1/4" (23.5 cm) diameter
- Hole cutout dimensions: 8" (20.3 cm) diameter
- Depth behind ceiling (5/8" drywall): 4-3/8" (11 cm)

### WARRANTY

- Lifetime Limited

E N G I N E E R E D B Y



©2010 Niles Audio Corporation. All Rights Reserved. Niles, the Niles logo and Blending High Fidelity and Architecture are registered trademarks of Niles Audio Corporation. MicroPerf and TCC are trademarks of Niles Audio Corporation. All other trademarks are the property of their respective owners. CS0311A